

号	主/备电带容性负载开关机	V1/10000 μF		标准	1	2	3	4	5	6	7	8	定			
		V2/5000 μF	8PCS													
10	备电欠压切断输出电压 (V)	21V ± 1V		8PCS	✓	✓	✓	✓	✓	✓	✓	✓	AC			
11	备电停止输出蜂鸣器告警 (min)	(90 ± 1min)		3PCS	✓								AC			
12	告警结束工作电流 (uA)	< 500uA		3PCS	330		340		340				AC			
13	输出端接地 (PE) 保护	产品正常		3PCS	✓		✓		✓				AC			
14	187 VAC	V1out	满载电压 (V)	27V ± 1V	8PCS	214	214	215	214	214	214	214	215	214	AC	
			V2out	满载电压 (V)	27V ± 1V	8PCS	214	214	215	214	214	214	214	215	214	AC
		V1out	空载电压 (V)	27V ± 1V	8PCS	213	213	214	214	213	213	213	214	215	213	AC
			满载电压 (V)	27V ± 1V	8PCS	215	215	215	215	215	215	215	215	215	215	AC
		V2out	空载电压 (V)	27V ± 1V	8PCS	214	214	215	214	214	214	214	214	215	214	AC
			满载电压 (V)	27V ± 1V	8PCS	215	215	215	214	215	215	215	215	215	215	AC
		功率 (W)			560 ± 5%	8PCS	213	213	214	213	213	213	214	214	213	AC
		效率 EFP			≥ 85%	8PCS	546	546	548	546	546	546	548	546	546	AC
		纹波电压系统 10A; 联动 10A			≤ 250mV	8PCS	86.39	86.66	86.57	86.66	86.52	86.25	86.43	86.8	AC	
		过流保护 (联动空载)			22-28A	8PCS	64	72	84	64	68	76	60	64	64	AC
过流保护 (系统空载)			11-14A	8PCS	72	76	80	68	76	68	76	68	68	AC		
16	220 VAC 50HZ	V1out	满载电压 (V)	27V ± 1V	8PCS	11.7	11.8	12.1	11.8	12.0	11.8	11.3	12.4	AC		
			V2out	满载电压 (V)	27V ± 1V	8PCS	214	214	215	214	214	214	215	214	AC	
		V2out	满载电压 (V)	27V ± 1V	8PCS	213	213	214	213	213	213	214	213	AC		
安规测试																
1	泄漏电流 AC234V		≤ 0.5mA	3PCS	0.18	0.19	0.20						AC			
2	耐压测试: P-S 2500Vac; LN-PE 2500Vac; S-PE 1500Vac			3PCS	✓	✓	✓						AC			
3	绝缘阻抗 ≥ 50M Ω 500VDC	I/P-O/P		3PCS	12.34A	13.24A	11.56A						AC			
		I/P-GND		3PCS	1746A	819A	1686A						AC			
4	接地电阻测试 12V/10A < 0.5 Ω	PE-外壳		3PCS	0.03	0.03	0.05						AC			

其它要求

备注:

最终判定	是否盖章 <input checked="" type="checkbox"/> 是 <input type="checkbox"/> 否	核准	审核	检验员
合格允收 <input checked="" type="checkbox"/> 拒收 <input type="checkbox"/> 特采 <input type="checkbox"/>		Shmz		刘莎

